LEDSION WALL PACK



Product Description

LEDSION led wall pack has a same beautiful look as traditional wall packs,but with over 110-130lm/W light efficiency, best aluminum heat dissipation sink. equipped with long lasting driver which last 50000hrs,ideal for replacing old wall packs 100-600W.

Application

Outdoor building, Wall area, General area and Security lighting etc







Electric Characteristic

Specification/Model	LS-WP41W	LS-WP60W	LS-WP80W	LS-WP100W	LS-WP120W	LS-WP150W	
LED Chips	Philip3030						
Input power	41W	60W	80W	100W	120W	150W	
Lumens output	3400-3500LM	7700-7800LM	9100-9200 Im	10000-11000Im	15000-16000 lm	18000-19500LM	
Efficiency	80-90M/W	120-130LM/W	110-120lm/w	100-110 lm/W	12 0-130LM/W	120-130LM/W	
CRI	71Ra						
Color Temperature	3000/4000K/5000K						
Input voltage	100-277V UL Driver						
Lighting beam	120D						
Power Factor	0.9						
Total Harmonic Distortion	13.4%						
lamps efficiency	90%						
Certificates	ETL,CETL,DLC						
Equivalent	100-150W MH/HPS	150-200W MH/HPS	250-300W MH/HPS	300-350W MH/HPS	350-450W MH/HPS	450-600W MH/HPS	



Talk to one of our LED consultants today! (800) 426-3938 • (319) 653 3198


info@sitlersupplies.com www.sitlersledsupplies.com

Ordering Information

Exsample:LS-WP41W-30K-N-T

Product	Power	Replacement	Color Temperature	Photocell	Furnish
LS-WP41W(5000K)	41W	100-150W MH/HPS			
LS-WP60W(5000K)	60W	150-200W MH/HPS	30K=3000K	N not photocell	WP=Wall Pack
LS-WP80W(5000K)	80W	250-300W MH/HPS	40K=4000K	Y yes photocell	
LS-WP100W(5000K)	100W	300-350W MH/HPS	50K=5000K	r yes photocett	
LS-WP120W(5000K)	120W	350-400W MH/HPS			
LS-WP150W(5000K)	150W	450-600W MH/HPS			

Photometri





Projected LED Lumen Maintenance


Operating hours	0	25000	50000
Lumen maintenace factor	1	0.91	0.8

Data references the extrapolated performance prohections for the WALLPACK LED platform in a 25 $^\circ\!C$ ambient,based on 10,000 hours of LED testing(tested per IESNA LM-80-08 and projected per IESNA TM-21-11)

Dimensions:







9.3"

After sale Service:

The product refers to electrics knowledge.Please don't disassemble it by yourself.If any quality problem happens, please contact the factory for warranty details NOTE:Actual performance may differ as a result of end-user environment and application.All values are without notice

Talk to one of our LED consultants today! (800) 426-3938 • (319) 653 3198 info@sitlersupplies.com www.sitlersledsupplies.com

